




NON-SPILLABLE SEALED RECHARGEABLE BATTERY


EV6130

☆ SPECIFICATION	☆ CHARACTERISTICS
● NOMINAL VOLTAGE : 6 V	● CAPACITY 25 °C / 77 °F
● NOMINAL CAPACITY(20 hrs) : 13 Ah	20 hr @ 0.65 A : 13 Ah
● DIMENSIONS	10 hr @ 1.17 A : 11.7 Ah
TOTAL HEIGHT : 101 mm (3.98 inches)	5 hr @ 2.08 A : 10.4Ah
CONTAINER HEIGHT : 95 mm (3.74 inches)	1 hr @ 7.8 A : 7.8 Ah
LENGTH : 151 mm (5.95 inches)	1 C @ 13 A : 6.5 Ah
WIDTH : 50 mm (1.97 inches)	● INTERNAL RESISTANCE(25°C, 77 °F) : 10 mΩ
WEIGHT : APPROX 2.10 kg (4.63 lbs)	● CHARGING VOLTAGE (25°C, 77 °F)
● MAX DISCHARGE CURRENT : 130 A (5 sec)	STANDBY USE : 2.275±0.025 V/CELL
● MAX SHORT- DURATION DISCHARGE CURRENT : 390 A(0.1 sec)	: (-3.3mV / °C / CELL)
● STANDARD TERMINALS : FO-02/FO-03	CYCLE USE : 2.45±0.05 V/CELL
● CONTAINER MATERIAL : GENERAL GRADE ABS	: (-5 mV / °C / CELL)
	● MAX CHARGING CURRENT : 3.9 A


Discharge Characteristics 25 °C (77 °F)



OPEN CIRCUIT VOLTAGE VS REMAINING CAPACITY



☆ Dimensions



☆ Terminal

