

P/N: ER26500
SIZE: C

HIGH CAPACITY BOBBIN LITHIUM CELL
Lithium Thionyl Chloride (Li/SOCI₂)

CROSS REFERENCE
LS26500, TL-5920

ELECTRICAL CHARACTERISTICS

(Typical values for cells stored one year or less at +30°C (86°F) max.)




Nominal voltage (@25°C):	3.6V
Rated capacity: (At 2mA, +25°C 2.0V cut off. Discharge capacity may vary with current drain, temperature and cut off voltage)	8.5Ah
Maximum recommended continuous current: (at 25°C to cut-off 2.0V)	200mA
Maximum pulse current: (Current value is obtained by discharging cells for 15 seconds to 2.0V at 50% discharge depth at 25°C)	400mA
Operating temperature range: (Operation at different temperatures may lead to changes in capacity)	-55°C / +85°C (-67°F / +185°F)
Cell diameter (max.):	26.2mm
Cell height (max.):	50.5mm
Typical weight:	52g

Features

- Stainless steel container
- Hermetic glass-to-metal sealing
- Extreme long operation
- Very low self discharge rate
- Wide range operation temperature
- UL Recognition File No. MH45994

Applications


- AMR / Utility metering
- Electronic toll collection
- Radio communication
- Alarms / security systems
- RF transmitters
- Medical equipment
- Memory back-up
- Automotive electronics



Available terminations

- /P: Axial leads
- /T, -/PT2: Radio pins
- /PT, -/TP: Polarized tabs

Custom terminations available upon request



Dimensions in mm

Product specifications are subject to change without prior notice. Any presentation in this data sheet concerning performance is for information purpose only and not warranties, either expressed or implied, of future performance.